

Series	FS	Warranty	1 Year
Volts	12	BCI	Grp 24
Cells	6		
Terminal Type		DT	
Included Hardware		Stainless Steel K-Lock Nut	
Size & Thread		5/16"-18	

### Charge

Charge Voltage Range	14.7-15 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	550
Marine Crank Amps (MCA) 32°F / 0°C	690
Reserve Capacity (RC @ 25A)	150 Minutes
Reserve Capacity (RC @ 75A)	43 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPS
@ 100 Hour Rate	<b>106 AH</b>	<b>1.06 A</b>
@ 20 Hour Rate	<b>85 AH</b>	<b>4.25 A</b>
@ 15 Hour Rate	<b>80 AH</b>	<b>5.33 A</b>
@ 10 Hour Rate	<b>72 AH</b>	<b>7.23 A</b>
@ 8 Hour Rate	<b>71 AH</b>	<b>8.82 A</b>
@ 5 Hour Rate	<b>69 AH</b>	<b>13.8 A</b>
@ 1 Hour Rate	<b>31 AH</b>	<b>30.6 A</b>

Amphere hour capacity ratings based on specific gravity of 1.280 at 25°C (77°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




SAI GLOBAL  
ISO 9001  
Quality

Weight	21.5 kg	47.5 lbs
Length	27.9 cm	11"
Width	17.1 cm	6.75"
Height Inc. Term.	23.8 cm	9.38"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	Plastic Strap

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

